

BLAKELY SOKOLOFF TAYLOR & ZAFMAN

A LIMITED LIABILITY PARTNERSHIP INCLUDING LAW CORPORATIONS

TELEPHONE (310) 207-3800

INTELLECTUAL PROPERTY LAW

OTHER OFFICES

FACSIMILE (310) 820-5988
(310) 820-527012400 WILSHIRE BOULEVARD
SEVENTH FLOOR
LOS ANGELES, CA 90025-1026ORANGE COUNTY/COSTA MESA, CA
SILICON VALLEY/SUNNYVALE, CA
DENVER, CO
PORTLAND/BEAVERTON, OR
SEATTLE, WABSTZ_MAIL@BSTZ.COM
WWW.BSTZ.COM**FACSIMILE TRANSMITTAL SHEET**

Deliver To: Examiner Ben Wang

Company: U.S. PATENT AND TRADEMARK OFFICE

Fax No.: (571) 270-2240

From: Joseph Lutz

Date: April 15, 2010

Number of Pages: 12 **(Including Cover Sheet)**

Operator: Si Vuong

Our Reference: 042390.P17829

SUBJECT: Application No. 10/714,465
Proposed Examiner's Amendment (not for entry)

REMARKS: Please see attached. Thank you.

CONFIDENTIALITY NOTE: The documents accompanying this facsimile transmission contain information from the law firm of Blakely, Sokoloff, Taylor & Zafman which is confidential or privileged. The information is intended to be for the use of the individual or entity named on this transmission sheet. If you are not the intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this faxed information is prohibited. If you have received this facsimile in error, please notify us by telephone immediately so that we can arrange for the retrieval of the original documents at no cost to you.

If you do not receive all the pages, or if there is any difficulty in receiving, please call: (310) 207-3800 and ask for the operator named above.

Attorney's Docket No. 042390.P17829

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Jinquan Dai, et al.

Application No. 10/714,465

Filed: November 14, 2003

For: **APPARATUS AND METHOD FOR
AUTOMATICALLY PARALLELIZING
NETWORK APPLICATIONS THROUGH
PIPELINING TRANSFORMATION**

Examiner: Ben C. Wang

Art Unit: 2192

Confirmation No.: 2488

PROPOSED EXAMINER'S AMENDMENT (not for entry)


Sir:

Applicants respectfully acknowledge with appreciation the Examiner's contacting of Applicants' representative Joseph Lutz via telephone on April 9, 2010 to place the claims in condition for allowance. Accordingly, Applicants submit herewith proposed amendments for the Examiner's review.

Respectfully submitted,

BLAKELY, SOKOLOFF, TAYLOR, & ZAFMAN LLP

Dated: April 15, 2010

By: 
Joseph Lutz, Reg. No. 43,765

AMENDMENTS TO THE CLAIMS (not for entry)

1. (Currently Amended) A method comprising:
 - configuring one or more processors into a D-stage processor pipeline;
 - constructing a flow network model ~~for the~~ for a sequential network application program;
 - selecting a plurality of preliminary pipeline stages from the flow network model;
 - modifying the preliminary pipeline stages to perform control flow and variable transmission therebetween for transforming the sequential network application program into D-pipeline stages that collectively perform an infinite packet processing stage (PPS) loop of the sequential network application program; and
 - executing the D-pipeline stages in parallel within the D-stage processor pipeline to provide parallel execution of the infinite PPS loop of the sequential network application program, wherein constructing the flow network model comprises:
 - assigning a unique source node and a unique sink node to the flow network model,
 - adding a program node to the flow network model for each ~~SSC node~~ strongly-connected component (SSC) node identified in the summary graph of the dependence graph,
 - adding a variable node to the flow network model for each variable that is defined and used by multiple program nodes,
 - adding a control node C to the flow network model for each SSC node identified in the summary graph of the dependence graph as a source of control dependence,
 - generating edges having an associated weight to connect corresponding program nodes to corresponding variable nodes,
 - generating edges having an associated weight to connect corresponding program nodes to corresponding control nodes, and
 - generating edges between the program nodes and one of the source node and the sink node; and

wherein generating edges having an associated weight to connect corresponding program nodes to corresponding variable nodes further comprises:

- (i) selecting a program node N that defines a variable node V,
- (ii) adding a definition edge from node N to node V with a weight VCost to the flow network model,
- (iii) repeating (i) - (ii) for each program node N that defines a variable node V,
- (iv) selecting a program node M that uses a variable node W,
- (v) adding an edge from the node W to the program node M with an assigned weight of infinity to the flow network model, and
- (vi) repeating (iv) - (v) for each program node M that uses a variable node W.

2. (Cancelled)

3. (Currently Amended) The method of claim 1, wherein constructing the flow network model comprises:

- transforming the application program into a static, single-assignment form;
- building a control flow graph for a loop body of the application program;
- building a dependence graph based on a summary graph of the control flow graph and identified, ~~strongly connected components (SCC)~~ SSC nodes of the control flow graph; and
- constructing the flow network model according to a summary graph of the dependence graph and identified SSC nodes of the dependence graph.

4-5. (Cancelled)

6. (Previously Presented) The method of claim 1, wherein generating edges having an associated weight to connect corresponding program nodes to corresponding control nodes comprises:

- (i) selecting a program node N that has an associated control node C;
- (ii) adding a definition edge from the selected node N to the associated control node C;

- (iii) associating a weight CCost to the edge;
- (iv) repeating (i) - (iii) for each program node that has an associated control node;
- (v) selecting a program node N having a controlled dependence on another program node M;
- (vi) associating M with the control node C;
- (vii) adding an edge from the associated control node C to the selected program node N;
- (viii) assigning a weight of infinity to the edge; and
- (ix) repeating (v) - (viii) for each node N that has a controlled dependence on another program node M.

7. (Previously Presented) The method of claim 1, wherein generating the edges between program nodes and one of the source node and the sink nodes comprises:

- (i) selecting a program node without predecessor node in the flow network model;
- (ii) adding an edge from the source node to the selected program node;
- (iii) assigning a weight of zero to the edge;
- (iv) repeating (i) - (iii) for each program node that has no predecessors;
- (v) selecting a program node that has no successors in the flow network;
- (vi) adding an edge from the selected program node to the sink node;
- (vii) assigning a weight of zero to the added edge; and
- (viii) repeating (v) - (vii) for each program node without a successor node in the flow network model.

8. (Previously Presented) The method of claim 1, wherein selecting the plurality of preliminary pipeline stages comprises:

cutting the flow network model into D-1 successive cuts, such that each cut is a balanced minimum cost cut.

9. (Original) The method of claim 8, wherein cutting is performed using an iterative balanced to push-relabel algorithm.

10. (Previously Presented) The method of claim 1, wherein modifying the preliminary pipeline stages comprises:

- (a) selecting a preliminary pipeline stage;
- (b) altering the selected preliminary pipeline stage to enable proper transmission of live variables and control flow to and from the selected preliminary pipeline stage; and
- (c) (a) – (b) for each preliminary pipeline stage to form the D-pipeline stages of a parallel network application.

11. (Currently Amended) An article of manufacture including ~~a machine computer~~ readable storage medium having stored thereon instructions which may be used to program ~~a system computer~~ to perform a method, comprising:

- configuring one or more processors into a D-stage processor pipeline;
- constructing a flow network model ~~for the~~ for a sequential network application program;
- selecting a plurality of preliminary pipeline stages from the flow network model;
- modifying the preliminary pipeline stages to perform control flow and variable transmission therebetween for transforming the sequential network application program into D-pipeline stages that collectively perform an infinite packet processing stage (PPS) loop of the sequential network application program; and

- executing the D-pipeline stages in parallel within the D-stage processor pipeline to provide parallel execution of the infinite PPS loop of the sequential network application program,

- wherein constructing the flow network model comprises:

- assigning a unique source node and a unique sink node to the flow network model,

- adding a program node to the flow network model for each ~~SSC node strongly-connected component (SSC) node~~ identified in the summary graph of the dependence graph,

- adding a variable node to the flow network model for each variable that is defined and used by multiple program nodes,

adding a control node C to the flow network model for each SSC node identified in the summary graph of the dependence graph as a source of control dependence,
generating edges having an associated weight to connect corresponding program nodes to corresponding variable nodes,
generating edges having an associated weight to connect corresponding program nodes to corresponding control nodes, and
generating edges between the program nodes and one of the source node and the sink node; and
wherein generating the edges between program nodes and one of the source node and the sink nodes comprises:

- (i) selecting a program node without predecessor node in the flow network model,
- (ii) adding an edge from the source node to the selected program node,
- (iii) assigning a weight of zero to the edge,
- (iv) repeating (i) - (iii) for each program node that has no predecessors,
- (v) selecting a program node that has no successors in the flow network,
- (vi) adding an edge from the selected program node to the sink node,
- (vii) assigning a weight of zero to the added edge, and
- (viii) repeating (v) - (vii) for each program node without a successor node in the flow network model.

12. (Cancelled)

13. (Currently Amended) The article of manufacture of claim 11, wherein constructing the flow network model comprises:

transforming the application program into a static, single-assignment form;
building a control flow graph for a loop body of the application program;
building a dependence graph based on a summary graph of the control flow graph and identified, ~~strongly connected components (SSC)~~ SSC nodes of the control flow graph; and

constructing the flow network model according to a summary graph of the dependence graph and identified SSC nodes of the dependence graph.

14. (Cancelled)

15. (Previously Presented) The article of manufacture of claim 11, generating edges having an associated weight to connect corresponding program nodes to corresponding variable nodes further comprises:

- (i) selecting a program node N that defines a variable node V;
- (ii) adding a definition edge from node N to node V with a weight VCost to the flow network model;
- (iii) repeating (i) - (ii) for each program node N that defines a variable node V;
- (iv) selecting a program node M that uses a variable node W;
- (v) adding an edge from the node W to the program node M with an assigned weight of infinity to the flow network model; and
- (vi) repeating (iv) - (v) for each program node M that uses a variable node W.

16. (Previously Presented) The article of manufacture of claim 11, wherein generating edges having an associated weight to connect corresponding program nodes to corresponding control nodes comprises:

- (i) selecting a program node N that has an associated control node C;
- (ii) adding a definition edge from the selected node N to the associated control node C;
- (iii) associating a weight CCost to the edge;
- (iv) repeating (i) - (iii) for each program node that has an associated control node;
- (v) selecting a program node N having a controlled dependence on another program node M;
- (vi) associating M with the control node C;
- (vii) adding an edge from the associated control node C to the selected program node N;

- (viii) assigning a weight of infinity to the edge; and
- (ix) repeating (v) - (viii) for each node N that has a controlled dependence on another program node M.

17. (Cancelled)

18. (Previously Presented) The article of manufacture of claim 11, wherein selecting the plurality of preliminary pipeline stages comprises:

cutting the flow network model into D-1 successive cuts, such that each cut is a balanced minimum cost cut.

19. (Original) The article of manufacture of claim 18, wherein cutting is performed using an iterative balanced to push-relabel algorithm.

20. (Previously Presented) The article of manufacture of claim 11, wherein modifying the preliminary pipeline stages comprises:

- selecting a preliminary pipeline stage;
- altering the selected preliminary pipeline stage to enable proper transmission of live variables to and from the selected preliminary pipeline stage;
- altering the selected preliminary pipeline stage to enable proper transmission of control flow to and from the selected preliminary pipeline stage; and
- repeating the selecting, altering and altering for each preliminary stage to form the D-pipeline stages of a parallel network application.

21. (Currently Amended) A computer-implemented method comprising:

- constructing a flow network model from a sequential network application program;
- cutting the flow network model into a plurality of preliminary pipeline stages; and
- transforming the preliminary pipeline stages to perform control flow and variable transmission therebetween to form D-pipeline stages that collectively perform an infinite packet processing stage (PPS) loop of the sequential network application program to enable parallel execution of the infinite PPS loop of the sequential network application program,

wherein transforming the preliminary application program stages comprises:

- (i) electing a preliminary application program stage,
 - (ii) selecting a control flow graph generated for the infinite PPS loop corresponding to the selected preliminary application program stage,
 - (iii) removing instructions from the control flow graph if the instruction is not contained within the selected preliminary pipeline stage,
 - (iv) transforming the selected control flow graph according to variables and control objects transmitted from the prior stage,
 - (v) reconstructing the PPS loop from the transformed control flow graph to form a pipeline stage, and
- repeating (i) - (v) for each preliminary pipeline stage to form D-pipeline stages of a parallel network application program; and

wherein transforming the selected control flow further comprises:

- selecting values for variables that are transmitted from a prior pipeline stage, and
- for each variable transmitted to a next pipeline stage, setting a value of the variable to a distinctive temporary following definition of the variable within the control flow graph.

22. (Cancelled)

23. (Previously Presented) The method of claim 21, wherein transforming the control flow further comprises:

- selecting values for control objects transmitted from a prior pipeline stage on entry to the control flow graph;
- for each control object received from the prior pipeline stage, constructing a conditional instruction using the control object; and
- replacing corresponding conditional nodes within the CFG with the conditional instruction.

24. (Cancelled)

25. (Previously Presented) The method of claim 21, wherein transforming the control flow graph further comprises:

for each control object to be transmitted to a next pipeline stage, placing an alternate value of the control object in each alternate successor node of a conditional node associated with the control object in the control flow graph; and

transmitting live set data to a next pipeline stage at exit of the control flow graph.

26. (Currently Amended) An article of manufacture including a ~~machine~~ computer readable storage medium having stored thereon instructions which may be used to program a ~~system~~ computer to perform a method, comprising:

constructing a flow network model from a sequential network application program;
cutting the flow network model into a plurality of preliminary pipeline stages; and
transforming the preliminary pipeline stages to perform control flow and variable transmission therebetween in order to form D-pipeline stages that collectively perform an infinite packet processing stage (PPS) loop of the sequential network application program to enable parallel execution of the infinite PPS loop of the sequential network application program,

wherein transforming the preliminary application program stages comprises:

- (i) electing a preliminary application program stage,
 - (ii) selecting a control flow graph generated for the infinite PPS loop corresponding to the selected preliminary application program stage,
 - (iii) removing instructions from the control flow graph if the instruction is not contained within the selected preliminary pipeline stage,
 - (iv) transforming the selected control flow graph according to variables and control objects transmitted from the prior stage,
 - (v) reconstructing the PPS loop from the transformed control flow graph to form a pipeline stage, and
- repeating (i) - (v) for each preliminary pipeline stage to form D-pipeline stages of a parallel network application program; and

wherein transforming the selected control flow graph further comprises:

for each control object to be transmitted to a next pipeline stage, placing an alternate value of the control object in each alternate successor node of a conditional node associated with the control object in the control flow graph, and
transmitting live set data to a next pipeline stage at exit of the control flow graph.

27. (Cancelled)

28. (Previously Presented) The article of manufacture of claim 26, wherein transforming the selected control flow graph further comprises:

selecting values for control objects transmitted from a prior pipeline stage on entry to the control flow graph;

for each control object received from the prior pipeline stage, constructing a conditional instruction using the control object; and

replacing corresponding conditional nodes within the control flow graph with the conditional instruction.

29. (Previously Presented) The article of manufacture of claim 26, wherein transforming the selected control flow graph further comprises:

selecting values for variables that are transmitted from a prior pipeline stage; and

for each variable transmitted to a next pipeline stage, setting a value of the variable to a distinctive temporary following definition of the variable within the control flow graph.

30-36. (Cancelled)